

## ***Rhythm Multi 3-1 Alternating System***



### **Main Feature:**


- 8" air cell mattress replacement
- 3-1 alternation and static
- Low air loss therapy
- Pulsation therapy
- Happy Heel – dial softness control at foot section
- Auto Firm provides immediate firm surface
- High vapor permeable and quilted nylon cover
- Optional cover available for fall prevention – built in 4.5" foam bolster with egress cutout.
- 2" convoluted foam base
- Cable Management System – provides conduit for powers cords to stay off floor, eliminate tripping hazards
- Integrated glide sheet to base cover for easy transferring
- Visual and audio alarm for low pressure and power failure with alarm mute function
- Keypad lock out function
- 10 electronic adjustable comfort settings
- Modularized design for air mattress
- Integrated power cable retainer
- SWL 600lb for 36", 750lb for 39", 800lb for 42", 1000lb for 48"
- Quick CPR deflation within 20 seconds

### **Clinical Considerations:**

- Multiple stage 1, 2, 3 and 4 pressure ulcer

Rhythm Multi Specification

Control Unit

Model Name	<b><i>Rhythm Multi</i></b>
Model No.	FC-PHR0009
Size (inch) L x W x H	17.7" x 6.8" x 10.8"
Weight (lbs.)	13.2
Cycle Time	3~95 min
Min Operating Pressure	10 +/- 3mmHg
Max Operating Pressure	61 +/- 4mmHg
Flow-rate	1200 L per minute
Rated Voltage	AC 110-120V
Rated Frequency	60 Hz
Fuse Rating	5A 250V
Max Current	5A
Classification	Class I, Type BF Not AP or AGP type 
Mode of Operation	Continuous
Environment (Temperature)	Operation: 15°C to 35°C (59F to 95F)
	Storage: 5°C to 60°C (41F to 140F)
Environment (Humidity)	Operation: 30% to 75% non-condensing
	Storage: 30% to 100% non-condensing
Standard	IEC 60601-1, CAN/CSA C22.2 No. 601.1, IEC 60601-1-2

Mattress

Model No	FM-PHR0007
Size (inch) L x W x H	80"L x 36"W x 10"H (42" and 48" widths available)
Weight	28.6 lbs.
Weight Capacity	600 lbs. (800 lbs. for 42"W and 1000 lbs. for 48"W)
Cell Number	18 cells
Cells Material	Nylon coated with PU
Cover Type	Zipper cover
Cover Material	Nylon woven fabric w/ PU coating finish; also available with a built in 4.5" raised foam bolster with egress cutout
Base Material	Woven Polyester fabric w/ PVC backing